

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims:

1. (Previously Presented) An implantable device for mounting to a patient's bone comprising:

a housing having an abutting surface configured to prevent osseointegration of said housing with the patient's bone;

one or more components mounted in said housing; and

at least a first protuberance and a second protuberance configured to attach to the patient's bone without insertion of the first or second protuberance into the bone;

wherein said first and second protuberances extend from said housing such that a longitudinal axis of the first protuberance and a longitudinal axis of the second protuberance are at opposing angles of about 45 degrees relative to an implant axis that is substantially orthogonal with the surface of the bone forming the pocket; and

wherein the protuberance is configured to osseointegrate with the patient's bone and separate at least a portion of said outer surface of said housing from the patient's bone when said housing is positioned within a pocket formed in the patient's bone such that the first and second protuberances abut a surface of the bone forming the pocket prior to osseointegration.

2. (Previously Presented) The implantable device of claim 1, wherein said housing abutting surface is configured to abut the patient's bone after osseointegration of the at least one protuberance.

3 -6. (Cancelled).

7. (Previously Presented) The implantable device of claim 1, wherein the implantable device is a tissue stimulating prosthesis.

8. (Previously Presented) The implantable device of claim 7, wherein said tissue stimulating prosthesis is a cochlear implant, and further wherein said one or more components comprise a stimulator unit of the cochlear implant.

9. (Previously Presented) The implantable device of claim 8, wherein a receiver antenna is operatively connected to said housing.

10-12. (Cancelled)

13. (Previously Presented) The implantable device of claim 1, wherein at least one of the protuberances is configured to be permanently implanted in the patient's bone.

14. (Previously Presented) The implantable device of claim 1, wherein at least one of the protuberances is configured to be extricated from the patient's bone subsequent to osseointegration.

15. (Cancelled)

16. (Previously Presented) The implantable device of claim 1, wherein at least one of the protuberances comprises at least one loop member.

17. (Previously Presented) The implantable device of claim 1, wherein at least one of the protuberances comprises at least one aperture.

18. (Previously Presented) The implantable device of claim 1, wherein at least one of the protuberances comprises at least one substantially smooth shaft.

19. (Previously Presented) The implantable device of claim 18, wherein the at least one substantially smooth shaft comprises a plurality of substantially smooth shafts each having a longitudinal axis, wherein the longitudinal axes of the shafts lie in different planes.

20. (Previously Presented) The implantable device of claim 22, wherein each of said protuberances comprises at least one threaded shaft.

21. (Previously Presented) The implantable device of claim 1, further comprising:
at least one elongate flange extending from said housing in a direction substantially parallel with a surface of the bone when the device is in an implant orientation, and wherein each of said protuberances is operationally disposed on one of said at least one flange so as to be laterally offset from said housing.

22. (Previously Presented) The implantable device of claim 21, wherein each of said of the protuberances is configured to be manipulated to extricate said protuberance from the bone subsequent to osseointegration.

23. (Previously Presented) The implantable device of claim 20, wherein each of said protuberances is a screw and wherein said threaded shaft is a part of said screw.

24. (Previously Presented) The implantable device of claim 21, wherein said at least one elongate flange is configured to prevent osseointegration.

25. (Previously Presented) The implantable device of claim 1, wherein at least one of the protuberances comprises at least one fastening member mounted to a support.

26. (Previously Presented) The implantable device of claim 25, wherein the at least one fastening member comprises one or more of the group consisting of:

- a screw;
- a clip; and
- a nail.

27. (Currently Amended) The implantable device of claim 1, wherein ~~said~~ at least one of the protuberances is formed of or coated with one of either titanium or titanium alloy.

28. (Currently Amended) The implantable device of claim 1, wherein ~~said~~ at least one of the protuberances comprises a protuberance surface treatment configured to encourage osseointegration.

29. (Cancelled)

30. (Previously Presented) The implantable device of claim 1, wherein said housing abutting surface is formed of a material coated with a biocompatible silicone.

31. (Previously Presented) The implantable device of claim 1, wherein said housing abutting surface is formed from at least one of a biocompatible metallic, ceramic and polymeric material.

32-39. (Cancelled)

40. (Currently Amended) The implantable device of claim 108, wherein ~~the~~ at least one of the protuberances comprises at least one loop member.

41. (Currently Amended) The implantable device of claim 108, wherein ~~the~~ at least one of the protuberances comprises at least one aperture.

42. (Currently Amended) The implantable device of claim 108, wherein ~~the~~ at least one of the protuberances comprises at least one substantially smooth shaft.

43. (Previously Presented) The implantable device of claim 42, wherein the at least one substantially smooth shaft comprises a plurality of substantially smooth shafts each having a longitudinal axis, wherein the longitudinal axes of the shafts lie in different planes.

44-48. (Cancelled)

49. (Currently Amended) The implantable device of claim 108, wherein ~~the~~ at least one of the protuberances comprises at least one fastening member mounted to a support.

50. (Previously Presented) The implantable device of claim 49, wherein the at least one fastening member comprises one or more of the group consisting of:

- a screw;
- a clip; and
- a nail.

51-88. (Cancelled)

89. (Previously Presented) The implantable device of claim 1, wherein the implantable device is a tissue stimulating prosthesis.

90. (Previously Presented) The implantable device of claim 89, wherein said housing and said one or more components comprise a stimulator unit of a cochlear implant.

91. (Currently Amended) The implantable device of claim 1, wherein each of said protuberances comprises at least one feature that facilitates osseointegration.

92. (Currently Amended) The implantable device of claim 1, wherein each of said protuberances is configured to prevent substantial relative lateral movement between the implantable device and the patient's bone.

93. (Previously Presented) A method for implanting an implantable device having a housing with an abutting surface configured to prevent osseointegration of the housing with a patient's bone and at least one osseointegrating protuberance extending from the housing, the method comprising:

forming a pocket on the patient's bone to receive the housing;

positioning the housing in said pocket such that the at least one protuberance is in direct contact with a surface of the patient's bone forming the pocket; and

allowing osseointegration of the at least one protuberance to occur without insertion of the at least one protuberance into the surface of the patient's bone forming the pocket,

whereby when the at least one protuberance is osseointegrated the abutting surface of the housing is not osseointegrated.

94. (Previously Presented) The method of claim 93, wherein the at least one protuberance comprises at least two protuberances, the method further comprising:

positioning said at least two protuberances adjacent surfaces of the patient's bone.

95. (Previously Presented) The method of claim 94, wherein the at least two protuberances each have a longitudinal axis that lies in a same imaginary plane at opposing angles relative to an implant axis that is substantially orthogonal with the housing abutting surface, the method further comprising:

positioning said at least two protuberances adjacent to the patient's bone such that the implant axis is substantially orthogonal to the patient's bone and such that at least a portion of the housing abutting surface is spaced from patient's bone before osseointegration occurs.

96. (Previously Presented) The method of claim 95, wherein the opposing angles between the longitudinal axes of the protuberances and the implant axis are each approximately between 5 and 85 degrees to provide a permanent implantation.

97. (Previously Presented) The method of claim 93, wherein the implantable device is a tissue stimulating prosthesis.

98. (Previously Presented) The method of claim 97, wherein the tissue stimulating prosthesis is a cochlear implant.

99. (Previously Presented) The method of claim 93, wherein forming a pocket comprises:

forming said pocket in the patient's bone, wherein the patient's bone is selected from the group consisting of a periosteum, skull, and a mastoid process.

100. (Previously Presented) The method of claim 93, further comprising:

extricating said at least one protuberance from the bone subsequent to osseointegration of the protuberance.

101. (Previously Presented) The method of claim 93, wherein the implantable device further comprises a flange extending from the housing in a direction substantially parallel with a surface of the bone when the device is in an implant orientation, wherein one or more of the at least one protuberance is disposed on the flange such that the one or more protuberances are laterally offset from the housing.

102. (Previously Presented) The method of claim 101, further comprising:
manipulating, subsequent to osseointegration, the one or more laterally-offset protuberances to extricate the one or more protuberances from the bone.

103. (Previously Presented) The method of claim 102, wherein the at least one elongate flange is configured to prevent osseointegration.

104. (Previously Presented) The method of claim 93, wherein the at least one protuberance is formed of or coated with one of either titanium or titanium alloy.

105. (Previously Presented) The method of claim 93, wherein the at least one protuberance comprises a protuberance surface treatment configured to encourage osseointegration.

106. (Previously Presented) The method of claim 93, wherein the housing abutting surface is formed of a material coated with a biocompatible silicone.

107. (Previously Presented) The method of claim 93, wherein the housing abutting surface is formed from at least one of a biocompatible metallic, ceramic and polymeric material.

108. (Previously Presented) An implantable device comprising:

 a housing to be secured to a patient's bone, said housing having an abutting surface configured to prevent osseointegration of said housing with the patient's bone;

 one or more components mounted in said housing; and

 at least a first and a second osseointegrating protuberance, each extending from said housing, wherein said first and second osseointegrating protuberance are configured to be placed in direct contact with a surface of the patient's bone but not within the patient's bone and further configured to gradually sink into the patient's bone during osseointegration of said protuberance; and

 wherein said first and second protuberances extend from said housing such that a longitudinal axis of the first protuberance and a longitudinal axis of the second protuberance are at opposing angles of about 45 degrees relative to an implant axis that is substantially orthogonal with the surface of the patient's bone.

109. (Previously Presented) The implantable device of claim 108, wherein said housing abutting surface is configured to abut the patient's bone after osseointegration of at least one of the protuberances.

110 -112. (Cancelled)

113. (Previously Presented) The implantable device of claim 108, wherein the implantable device is a tissue stimulating prosthesis.

114. (Previously Presented) The implantable device of claim 108, wherein at least one of the protuberances is configured to be extricated from the patient's bone subsequent to osseointegration.

115. (Previously Presented) The implantable device of claim 108, further comprising:

at least one elongate flange extending from said housing in a direction substantially parallel with a surface of the patient's bone when the device is in an implant orientation, and wherein each of said protuberances is operationally disposed on one of said at least one flange so as to be laterally offset from said housing.

116 – 118. (Cancelled)